



PL-E60P 60W 1:1

DMX

**IP54** 

21mm

thin



PL-E90P 90W 2:1

DMX

IP54



### **Edge SMD-LEDs**

Mount SMD-LEDs on the side of the light, to make the light only 21mm thickness with diffuser.

The innovative bottom reflection glass has laser dots with calculated spaces, so that the multi angles of edge light will be converged on the laser dots, and output 90° to the front with minimum light lost.

Edge Mounted SMD LEDs



Edge Mounted SMD LEDs

Reflection glass with calculated laser dots



### **IP54 Weather Proof**

Model	Test Item	Test Result	Report No.
PL-E60P	Degrees of protection	PASS	WT193600427
PL-E90P	provided by enclosure (IP54)	PASS	WT193600428

Recommended IP54 batteries:



#### PB-R160S+

160Wh 150W/12A load 1.5m drop proof IP54 proof



PB-R290S+

290Wh 200W/16A load 1.5m drop proof IP54 proof



# **Accessories and Package**



Optional barn door LA-HE60: for PL-E60P LA-HE90: for PL-E90P



Optional 40° Honeycomb LA-GE60: for PL-E60P LA-GE90: for PL-E90P



Provide 3-light Kit with Trolley case, Including Light Stands and Power adaptors



## **Specifications**

Model	PL-E60P	PL-E90P
Input votage	DC 11-36V	DC 11-36V
Power	60W	90W
Illuminance	1500Lux @ 1m	2200Lux @ 1m
Color Temp	2700K-6500K	2700K-6500K
Color rendering	CRI 98; TLCI 99	CRI 98; TLCI 99
IP class	IP54	IP54
DMX	DMX512 in&out	DMX512 in&out

SWIT Electronics Co., Ltd. +86-25-85805753 http://www.swit.cc Email: contact@swit.cc SWIT Electronics America, Inc 1-(408)260-8258 http://www.switusa.com Email: info@swit.us SWIT Electronics Europe GmbH +49(0)20659799339 http://www.switeu.com Email: info@swit-europe.com





Facebook Page