
Camgear V6OS EFP 4-Bolt Flat Base

Specifications

Model Number	V60S EFP
Maximum Payload	70 kg/154.3 lbs
Counterbalance Range	0-70 kg/0-154.3 lbs (at C.O.G 125 mm)
Camera Platform Type	Euro plate (Camgear WP-6)
Sliding Range	120 mm/4.7 in
Camera Plate	Double 3/8" screw
Counterbalance System	13 steps (1-10 & 3 Adjusting levers)
Pan & Tilt Drag	10 steps (1-10)
Pan & Tilt Range	Pan: 360° / Tilt: +90/-75°
Temperature Range	-40°C to +60°C / -40 to +140°F
Levelling Bubble	Illuminated Levelling Bubble
Weight	12.66 kg/27.9 lbs
Tripod Fitting	4-Bolt Flat Base

- Selectable 10 positions pan 6 tilt drag including zero position, offer operators silky smooth movement, precise motion tracking and shake-free shot.
- Selectable 10 position counterbalance dial wheel plus center-added 3 more position, thanks to 10+3 counterbalance position system, it can do much finer adjustment for the camera to reach the perfect counterbalance.
- Perfect solution for various heavy EFP applications.
- Equipped with Euro plate quick-release system, which enables faster set-up of camera. It also has sliding knob to allow easy adjustment of the horizontal balance of camera.
- Equipped with assembly lock mechanism, which ensures safe set-up of equipment.



Camgear V60S EFP MS AL 4-Bolt Flat Base

Tripod System incl. V60S EFP Fluid Head, Aluminum Tripod & Mid Level Spreader. **SKU:** CMG-V60S-EFP-MS-AL-TRISYS



System Configuration

V6OS EFP Fluid Head Camgear Studio/OB Heavy-Duty Tripod 2 PB-3 Telescopic Pan Bars (Left & Right) MSP-3 Heavy-Duty Mid Level Spreader

Weight	28.82 kg/63.5 lbs
Maximum Height	1.61 m/63.4 in
Minimum Height	1.03 m/40.6 in
Section	1 Stage