bebob



A98micro rechargeable li-ion Battery User Manual

WE STRONGLY RECOMMEND THAT YOU READ THIS INSTRUCTION BEFORE USING YOUR BEBOB A98MICRO BATTERY! PLEASE KEEP THIS MANUAL FOR FUTURE REFERENCE

Features

- A high capacity battery which is compact and lightweight. Direct fitting to a camera via A-Mount (Gold-mount compatible)
- Five-step LED power indicator (100% 80% 60% 40% 20%).

Safety instructions

- Only for professional use! Keep batteries out of reach of children and personnel that has not been instructed in the use of high capacity Lithium-ion batteries!
- Use only with recommended charger.
- Keep the battery dry and do not immerse in water.
- Never open the case of the battery.
- Do not expose to temperature over 60°C.
- Do not expose the battery to fire! May explode if thrown into fire!
- Maximum Load 10.0A.
- Do not put the battery on a device when the red charging LED flashes.
- Handle with care! Do not throw! Do not drop!

Charging

- Wait 30 Minutes after discharge before you put the battery on a charger.
- The bebob A98micro battery can be charged with an external bebob charger (or equivalent) with Lithium-ion (Li-ion) charging ability.
- Approximate charge time may vary depending on charger and temperature.
- bebob A98micro can be charged in ambient temperature for optimum performance at 10°C 30°C.
- bebob A98micro batteries can be recharged in any charge condition.

bebob factory GmbH – Höglwörtherstr. 350 – D-81379 München – Tel.: +49 89 27818282 www.bebob.de

Discharging

- Maximum load is 10.0A. When using the battery with video or lighting equipment, power consumption of the equipment must be 10.0A or below. For the protection of the battery, a load of 10.0A or over may activate the internal protection circuit and stop supply of power. In this case the status led will turn red.
- The battery can be used in ambient temperature of 20°C + 55°C.

Storage

- Storage temperature range is 20°C ~ + 35°C (<85% humidity).
- To store the battery for a long period (longer than 4 Weeks), the battery should be charged between 50% and 75%. The battery should be recharged every 4 Weeks.
- After storage some self-discharge will occur. Before re-use it is advisable to recharge the battery fully.

Camera Data Communication

- Blue leds: Arri/Sony Data Protocol
- Red leds: Red Data Protocol
- To switch between both status, press the Check button for 5s


Status led

- Status led lighting Green: Full Capacity over 70% of New
- Status led lighting Yellow: Full Capacity between 50% and 70% of New
- Status led lighting Red: Full Capacity under 50% of New


Flash Light

• To switch On/Off press the Check Button Twice

bebob factory GmbH – Höglwörtherstr. 350 – D-81379 München – Tel.: +49 89 27818282 www.bebob.de



20





Specifications

Model	A98micro
Mount	A-Mount (Gold-mount compatible)
Capacity	6,8Ah; 98Wh
Voltage	14,4V DC
Maximum Output Voltage	16.8 V DC
End Voltage	12.0 V
Cells	Lithium-Ion Trimix made in Japan
Max. Discharge Current	10.0A
Twist D-Tap	14.4V unreg. Max. 5A
USB Port	5V, 1.0A
Fuel Gauge	5-Step LED
Weight	0,55 Kg
Dimensions (WxHxD)	75x101x48mm
Chargers	bebob, idx, sony, pag
Charging time (bebob AS2/AS4)	2 Hours
Operating Temp. Range	
Charge	+ 10°C ~ + 30°C recommended
Discharge	- 20°C ~ + 55°C
Storage	- 20°C ~ + 35°C (<85% RH)

bebc

Warranty

- The A98micro is covered by a 2 years unconditional warranty on all parts, except the cells.
- The cells are covered by a 1 year warranty, 70% of the original capacity.
- For warranty issues or if you have any additional questions, please contact the appropriate bebob distributor listed at <u>www.bebob.de</u>.

Disposal

• The A98micro battery has to be disposed within a dedicated collection container for used device batteries. Please be aware that only empty batteries are allowed for disposal in collection containers. In case the battery is not completely discharged, precautions against a potential short-circuit have to be taken.

bebob

Transport as of April 1st 2016

This Summary reflects our current Knowledge.

1. Transport by Commercial Airline / Carry-on Luggage

- You can transport in your **carry-on luggage** a A98micro attached to the camera or equipment it powers.
- You can transport in your **carry-on luggage** an unspecified number of spare A98micro:
 - Put tape over the contacts.
 - Put each single battery in a plastic bag before packing it in your carry-on luggage
- A98micro do not need to be discharged to 30% SoC for transport as personal luggage, this is only a requirement of cargo shipments.
- Carry a copy of the bebob UN Transport Documentation and A98micro UN Certificate
- We recommend that you confirm with your carrier of choice, to determine any further restriction or local policies, before travelling. You will find the actual regulation of your carrier of choice in the bebob transport information system <u>www.fly-</u> <u>lithium.com</u>,

2. Transport by Commercial Airline / Checked-in Luggage

- You can transport in your checked-in luggage a A98micro attached to the camera or equipment it powers and a maximum of 3 A98micro spare packed in the same piece of luggage
- A98micro do not need to be discharged to 30% SoC for transport as personal luggage, this is only a requirement of cargo shipments.
- Carry a copy of the bebob UN Transport Documentation and A98micro UN Certificate
- We recommend that you confirm with your carrier of choice, to determine any further local restriction or policies, before travelling. You will find the actual regulation of your carrier of choice in the bebob transport information system <u>www.fly-</u> <u>lithium.com</u>,

3. Transport as air-, road- and sea-freight

- Li-Ion batteries, and so bebob A98micro, when shipped by air, road or sea are classified as dangerous goods class 9 and subject to special UN certified packaging.
- Air transport authority training and authorisation (PK 1) are required for packing any more than 2 A98micro, for an air cargo shipment.
- Li-lon batteries for air cargo must have a state-of-charge of no more than 30% for shipping, means only one out of the five fuel gauge led lights up.
- We recommend that you confirm with your carrier of choice, to determine any further local restriction or policies, before travelling. You will find the actual regulation of your carrier of choice in the bebob transport information system www.fly-

bebob factory GmbH – Höglwörtherstr. 350 – D-81379 München – Tel.: +49 89 27818282 www.bebob.de



lithium.com,

bebob factory GmbH – Höglwörtherstr. 350 – D-81379 München – Tel.: +49 89 27818282 www.bebob.de

October 2018