

PEARL NANO

The perfect-fit streamer and recorder







Pearl Nano™ Portable and versatile hardware encoder

Pearl Nano offers the ultimate blend of portability and versatility with a refined yet robust feature set that includes ingestion, encoding, HDMI pass-through, and recording.


CONNECT YOUR SOURCES



PEARL NANO



OUTPUT YOUR VIDEO



Fine-tuned for your productions

Streamline your setup with the ability to directly connect HDMI and SDI video sources and professional XLR or RCA audio to Nano along with Power over Ethernet Plus (PoE+). For zero-latency display of video sources on in-room monitors, Nano also features a built-in HDMI pass-through.



Flexible recording and storage

Nano makes it easy to record, transfer, and back up files with a variety of storage options.

Remove

An SD card slot on the front of the device allows for removable storage.

Expand

Need more local storage? Just add an M.2 SSD to Nano's expansion bay.

Attach

Nano can automatically transfer recorded files to a USB drive, local server, or network-attached storage device.




Control Nano your way

Use Pearl Nano's front screen for basic configuration and control, jump into the browser-based interface or local console to access all the features this small but mighty encoder has to offer, or centralize configuration and monitoring with Epiphan's cloud-based platform.

Key functions at your fingertips

Nano's front screen offers quick access to essential functions including basic configuration and easy streaming and recording. During events, the built-in screen serves as at-a-glance verification of your audio level and video program for production peace of mind.



Cloud-based configuration and monitoring

Epiphan Cloud streamlines configuration and monitoring of multiple Pearl Nanos and other Epiphan hardware with centralized access to key device statistics including operational status, system load, unit temperature, available storage, and overall health.

Elevate your productions

Build a beautiful layout for your video program with Nano's powerful custom layout designer. Create anything from simple picture-in-picture layouts to eye-popping compositions featuring dynamic backgrounds and other custom graphics – whatever suits your event best.



Ideal for SRT contributions

The compact and lightweight Pearl Nano supports Haivision's open-source Secure Reliable Transport (SRT) protocol for secure, high-quality, low-latency video streaming over any given network.

Pair with Panopto or Kaltura

Deep integration with Panopto and Kaltura lets you start and stop scheduled streaming or recording events using Nano's built-in screen and controls. The system can also push recordings to a user's folder on either platform to save administration time after events.



Small size, big capabilities



Screen for monitoring and config

Use the front screen for basic configuration/control and confidence monitoring



HDMI pass-through

Display video sources on in-room monitors with zero latency



HDMI and SDI video inputs

Directly connect HDMI and/or SDI video sources to Nano



XLR professional audio and RCA

Connect professional audio equipment with line-level XLR



Custom layout builder

Enhance your video program with a tailored layout



SRT encoding and decoding

Stream via SRT or use as a compact SRT contribution encoder



Key features

- Front screen for basic configuration/control and confidence monitoring
- Inputs for HDMI and SDI, line-level XLR and RCA
- HDMI program out and pass-through for zero-latency content display
- Custom layout builder for a tailored video program
- Intuitive browser-based UI and local console
- Cloud-based configuration and control via Epiphan Cloud
- SRT, HLS, MPEG-DASH, RTMP, and RTMPS streaming protocol support
- Comprehensive integration with Kaltura and Panopto
- Power over Ethernet Plus (PoE+) and DC power
- SD card slot for removable storage
- Expansion bay for user-supplied M.2 SSD
- USB input for attached storage
- 802.1x network access control
- Lightweight Directory Access Protocol (LDAP)
- Secure Sockets Layer (SSL)



Video inputs	Connectors:	1 × HDMI™, 1 × 12G SDI, 1 × USB 3.0 (coming soon)
	Network inputs:	SRT and RTSP
Audio inputs	Connectors:	2 × XLR pro line level (stereo pair or two mono), 1 × SDI, 1 × HDMI, 1 × RCA
	Audio gain control:	0 dB to +30 dB
Video outputs		1 × HDMI pass-through, 1 × HDMI program out
Video encoding	Codecs:	H.264, H.265 (coming soon as a paid upgrade)
	Color resolution:	4:2:0
	Resolution:	User selectable up to 1920 × 1200 (4K coming soon as a paid upgrade)
Streaming protocols		RTMP/RTMPS, SRT, HLS, MPEG-DASH, RTSP, MPEG-TS, UPnP
Encoded programs		1 × 1080p program at 30 fps (with up to 2 Full HD sources; 4K coming soon as a paid upgrade)
Audio encoding		MP3, PCM, and AAC (sampling 16 to 48 kHz with bitrate up to 320 kbps)
Network		1 × 10/100/1000 Ethernet port (RJ45) 802.1x network security and certificate management
Storage	SD card:	Up to 512 GB EXT4
	Internal storage:	SATA M.2 2280 SSD (M Key connector)
	Local USB:	Automatic or manual copy via 1 USB 3.0 port
	Network storage:	FTP, SFTP, SCP, RSYNC, CIFS, AWS, or WebDav servers
Recording formats		AVI, MP4, MOV, or MPEG-TS
Control		Browser-based Admin panel, front screen and control keys, remote login, HTTP, and RS-232 APIs
Dimensions (W × D × H)		8 1⁄8" × 5 7⁄8" × 1 5⁄8" (206 mm x 149 mm x 41 mm), 2 lbs (907 g)

Your address and contact information here.

™ and © 2020 Epiphan Systems Inc. All rights reserved.

Epiphan, Epiphan Video, Epiphan Systems, its products names and logos are tradenames or trademarks of Epiphan Systems Inc. All other company, interface and product names and logos are trademarks or registered trademarks of their respective owners in certain countries. Product descriptions and specifications regarding the products in this document are subject to change without notice.