
Camgear V35P EFP Payload 45kg Bowl 150mm



Specifications

Model Number	V35P
Maximum Payload	45 kg/99 lbs
Counterbalance Range	0-42 kg/0-92.6 lbs (at C.O.G 125 mm)
Camera Platform Type	Mini Euro plate (Camgear WP-5)
Sliding Range	120 mm/4.72 in
Camera Plate	1/4", 3/8" screw
Counterbalance System	11 steps (1-8 & 3 Adjusting levers)
Pan & Tilt Drag	8 steps (1-8)
Pan & Tilt Range	Pan: 360° / Tilt: +90/-75°
Temperature Range	-40°C to +60°C / -40 to +140°F
Levelling Bubble	Illuminated Levelling Bubble
Weight	7.03 kg/16.1 lbs
Bowl Diameter	150 mm

- Selectable 8 steps pan & tilt drag including zero position offer operators silky smooth movement and precise motion tracking and a shake-free shot.
- Selectable 11 position counterbalance, thanks to newly featured 3 added position, it can do much finer adjustment for the cameras to reach the perfect balance.
- Equipped with assembly lock mechanism, which ensures safe set-up of equipment.
- Perfect solution for EFP and field-based HD production and studio application. It supports most portable broadcast cameras and camcorders in heavy configuration and studio applications with teleprompter or compact studio lens.
- Quick-release mini Euro plate enables faster set-up of camera.



Camgear V35P EFP GS CF BOWI 150MM

Tripod System incl. V35P Fluid Head, Carbon Fiber Tripod & Ground

SKU: CMG-V35P-GS-CF-TRISYS





System Configuration

V35P Fluid Head EFP150/CF2 2-Stage Carbon Fiber Heavy-Duty EFP Tripod 2 PB-2 Telescopic Pan Bars (Left & Right) GS-2 Ground Spreader Tripod Bag

Weight	12.8 kg/28.2 lbs
Maximum Height	1.83 m/72 in
Minimum Height	0.75 m/29.5 in
Transport Length	0.99 m/39 in
Section	2 Stages



System Configuration

V35P Fluid Head EFP150/CF2 2-Stage Carbon Fiber Heavy-Duty EFP Tripod 2 PB-2 Telescopic Pan Bars (Left & Right) MSP-2 Mid Level Spreader RF-1 Rubber Feet (x3) Tripod Bag

Weight	13.24 kg/29.2 lbs
Maximum Height	1.76 m/69.3 in
Minimum Height	0.79 m/31.1 in
Transport Length	0.99 m/39 in
Section	2 Stages