

The Attached MSDS, represents the chemical construction of the manufactured cells used within Hawkwoods Lithium-Ion battery listed below.

## Model:

VL-M150D

# **Description:**

Mini V-Lok 14.4V 150Wh Data Lithium-Ion battery

# **Chemical Product and Company Identification**

**Product Information:** Lithium-Ion Battery (All models manufactured by Hawkwoods.)

Manufacturer: HAWK-WOODS LTD, BRISCALL HOUSE

KINGSNORTH INDUSTRIAL ESTATE, WOTTON ROAD

ASHFORD, KENT, TN23 6LN

**Emergency Tel:** +44 (0)1233 638715

Emergency Overview May explode in a fire which could release hydrogen fluoride gas, Use extinguishing media

suitable for materials burning in fire.

### **Composition Information**

Lithium-lon Cylindrical Cell Hazardous Ingredients	%	CAS Number
Aluminium Foil	2-10%	7429-90-5
Nickel compound ( Proprietary )	0-25%	-
Manganese compound ( Proprietary )	0-15%	-
Cobalt compound ( Proprietary )	4-50%	-
Styrene-Butadiene-Rubber	< 1%	-
Polyvinylidene Fluoride (PVDF )	< 5%	24937-79-9
Copper Foil	2-10%	7440-50-8
Carbon ( Proprietary )	10-30%	7440-44-0
Electrolyte ( Proprietary )	10-20%	-
Stainless Steel, Nickel and inert materials	Remainder	N/A



#### **Hazards Identification**

Primary routes of entry & Symptoms of Exposure

\*If exposure to internal materials within cell due to damaged outer casing, the following actions are recommended.

Skin Contact: No Effect under Rountine handling and use Not a health hazard *Wash area thoroughly with soap and water and seek Medical attention	NO	Eye Contact:  No Effect under Rountine handling and use  Not a health hazard  *Rinse eyes with water for 15 minutes and seek medical attention.	NO
Ingestion: No Effect under Rountine handling and use If Swallowed, Obtain medical attention immediately *Drink milk/water and induce vomiting; seek medical attention.	NO	Inhalation:  No Effect under Rountine handling and use  Not a health hazard  *Leave area immediately and seek medical attention.	NO
Skin Absorbtion: No Effect under Rountine handling and use Not a health hazard	NO	Reported as carcinogen:	N/A

#### Fire fighting measures

General hazard: Cell is not flammable but internal organic material will burn if the cell is

Incinerated. Combustion products include, but are not limited to hydrogen fluoride,

Carbon monoxide and carbon dioxide.

**Extinguishing Media:** Use extinguishing media suitable for the materials that are burning.

Special Firefighting: If possible, remove cell(s) from fire fighting area. If heated above 125°C, cell(s) may explode/vent.

Firefighting Equipment: Use NIOSH/MSHA approved full-face self-contained breathing apparatus (SCBA) with full

protective gear.

#### **Accidental Release Measures**

On Land: Place material into suitable containers and call local fire/police department.

In Water: If possible, remove from water and call local fire/police department.Handling: No special protective clothing required for handling individual cells.

Storage: Store in a cool, dry place.

#### **Exposure controls / Personal protection**

**Engineering controls:** Keep away from heat and open flame. Store in a cool dry place.

**Respirator:** Not required during normal operations. SCBA required in the event of a fire.

**Eye/Face protection:** Not required beyond safety practices of employer.

Gloves: Not required for handling of cells.

Foot protection: Steel toed shoes recommended for large container handling.



#### **Physical and Chemical Properties**

State	Solid	State	Solid
Odor	N/A	PH	N/A
Vapor pressure	N/A	Vapor density	N/A
Boiling point	N/A	Solubility in water	Insoluble
Specific gravity	N/A	Density	N/A

### **Stability and Reactivity**

Reactivity: None.

**Incompatibilities:**None during normal operation. Avoid exposure to heat, open flame and corrosives.

**Hazardous Decomposition:** None during normal operating conditions. If cells are opened, hydrogen fluoride and carbon

Monoxide may be released.

Conditions to avoid: Avoid exposure to heat and open flame. Do not puncture, crush or incinerate.

### **Physical and Chemical Properties**

This product does not elicit toxicological properties during routine handling and use.

Sensitization Teratogenicity	NO
Reproductive	NO
Toxicity	NO
Acute toxicity	NO

( If the cells are opened through misuse or damage, discard immediately. Internal components of cell irritants and sanitizers. )

#### **Ecological Information**

Some materials within the cell are bioaccumulative. Under normal conditions, these materials are contained and pose no risk to persons or the surrounding environment.

#### **Disposal considerations**

California regulated debris. RCRA Waste code: Non-regulated. Dispose of according to all federal, state and local regulations.

#### **Transport Information**

Lithium-lon batteries are considered to be "Rechargable batteries" and meet the requirements of transportation by the U.S Department of Transportation (DOT), International Civil Aviation Administration (ICAO).



Even classified as lithium ion batteries (UN3480), 2017 IATA Dangerous Goods Regulations 53nd edition Packing Instruction 965 Section II is applied. The Product is handled as Non-Dangerous Goods by meeting the following Requirements. (1)

## 100W and under

- Shippers Declaration required in net weight KG.
- UN specification packaging required (PGII standards)
- Class 9 label required
- · Dangerous goods surcharge

## Over 100W

Lithium ion cells and batteries offered for transport are not subject to other additional requirements of the UN Regulations if they meet the following; (1) - (5)

- **1.** For cells, the Watt-hour rating is not more than 20Wh.
- **2.** For batteries, Watt-hour rating is not more than 100Wh.
- **3.** Each cell or battery is of the type proven to meet the requirements of each test in the UN Manual of Tests and criteria Part 3 subsection 38.3.
- **4.** Each cells comply with Special Provision A154.
- 5. Quantity per Package shall not exceed 10kg

Hawkwoods products have been tested according to the UN Manual of Tests and Criteria.

#### **Physical and Chemical Properties**

No.	Test Item	Criteria	Result
Test 1	Altitude Simulation	- No Leakage, venting, disassembly, rupture and No fire.  - Measuring mass before/after each test ( If M>5g, less than 0.1% )  - Measuring voltage before/after each test. ( More than 90% )	PASS
Test 2	Thermal test		PASS
Test 3	Vibration		PASS
Test 4	Shock		PASS
Test 5	External Short Circuit	- No disassembly, rupture and fire within six hours of this test.  - Max. Temperature should not exceed 170c	PASS
Test 6	Impact		PASS
Test 7	Overcharge	- No disassembly and fire within seven days of test.	PASS