



ATEM156-CO 15.6" MULTIVIEW 4K CARRY-ON DIRECTOR MONITOR

Designed for film crew, satisfied the field monitoring and post-production needs for director



- 1920X1080 FHD Resolution
- Quad View
- PIP/PBP Dual View
- 4xHDMI In/Out
- Aluminum Metal Frame
- Portable Aluminum Case

15.6" LCD, Full HD 1920x1080

The more realistic the shooting picture is, the more accurate the post-editing and production.

- Full HD 1920X1080
- 8Bit 16.7M Colors
- 800:1 High Contrast
- IPS 170° View Angle



4 X 4K HDMI Inputs and Outputs

Connect up to 8 cameras, game consoles or computers!



4K HDMI Format Supports

• 4096X2160p 24Hz/ 3840X2160p (30/29.97/25/24/23.98Hz)

Professional Monitoring Functions

Has set up professional monitoring functions to help you improve the shooting efficiency.

- Quad View
- Peaking Filter
- False Colors
- Image Flip 90°/180°/270°
- Anamorphic Mode
- Image Freeze
- Zoom-in
- Center Marker
- Screen Marker
- Pixel-to-Pixel
- Check Field
- Color Temperature

Ideal Monitor for Live Broadcasting

The multiview feature and the portable aluminium case of ATEM156-CO makes the multi-camera live broadcasting easier and more convenient.



Specification

Description	15.6" Carry-on Director Monitor Quad Split Display
Model	ATEM156-CO
Screen size	15.6" IPS
Resolution	1920×1080 pixels
Display Colors	16.7M colors (8-bits)
Dot pitch	0.17925 (H) X 0.17925 (V) mm
Aspect Ratio	16:9
Brightness	250 cd/m ²
Contrast	800:1
Backlight	LED
Viewing Angle	85°/85°(L/R) 85°/85°(U/D)
Inputs	HDMIx4 (support 4K 30Hz)
Outputs	HDMIx4 (support 4K 30Hz)
Audio	3.5mm Stereo Headphone, Speaker
HDMI Support Format	480i/576i/480p/576p 720p (60/59.94/50/30/29.97/25/24/23.98) 1080i (60/59.94/50) 1080p (60/59.94/50/30/29.97/25/24/23.98) 3840×2160p (30/25/24), 4096×2160p (24)
Power Consumption	≤12W
Input Voltage	DC12~24V
Operating Temperature	-10°C~50°C
Storage Temperature	-20°C~60°C
Unit Size	372L×262H×28.4D (mm)(without aluminum case)
Unit Weight	1.57kg (without aluminum case)
Standard Accessory	3A DC Power Adapter, V-Mount Battery Plate, U-shaped Bracket, Mini/ Micro HDMI to HDMI Cable, Operation Manual

Zhangzhou Seetec Optoelectronics Technology Co., Ltd

E-mail: sales@seetec.com.cn

Tel: +86-596-2672627

Website: www.feelworld.com.cn

Fax: +86-596-2672617

www.seetec.com.cn