

HD-NDI-MINI

NDI®|HX Compatible FHD WP Lipstick Camera

The most discreet NDI|HX camera has to be the HD-NDI-MINI. With its weatherproof barrel design, the HD-NDI-MINI is protected where it is stashed. From the highs of rafters, to the inside of pylons, the HD-NDI-MINI is the ultimate addition to any NDI workflow.



KEY FEATURES:







APPLICATIONS:









MACHINE VISION

SCIENCE RESEARCH

*NDI® is a registered trademark of Newtek, Inc.

OUTDOOR EVENTS

MOTION CAPTURE

POV SHOTS

WWW.AIDAIMAGING.COM



MAIN FEATURES

- Full-HD 1/3" Progressive Scan CMOS sensor capable of 1080 60p NDI[®] |HX Video.
- Accessible Web UI to stream directly to social media platforms
 and control image parameters over IP.
- Compact design used for discreet, hard to reach POV shots unobtainable by larger cameras.

SPECIFICATIONS

VIDEO

| Image Sensor | 1/3" Progressive CMOS |
|------------------------|-----------------------------------|
| Sensor Size | 5.346mm x 3.003mm (16.9) |
| Effective Pixels | Horizontal: 1920, Vertical: 1080 |
| Pixel Size | 2.75 μm (H) x 2.75 μm (V) |
| Resolution | 1080p, 1080i, 720p |
| Resolution Rate | 1080 60p/59.94/50p/30p/29.97p/25p |
| | 24p |
| | 1080 60i/59.94i/50i |
| | 720 60p/59.94p/50p |
| Output | IP (NDI HX/SRT/RTMP/RTSP) |
| Color Space | 4:2:2 (YCbCr) 10bit |
| Min Illumination | 0.2Lux (day), 0.1Lux (Night) |
| White Balance | Auto & Manual (9000 - 11,000 K) |
| | |

- M12 type lens for an even smaller form factor
- Weatherproof rating allows for extra protection against environmental elements.
- Barrel design for better weatherproofing and fitment.
- Perfectly suited for outdoor shots any new or existing NDI $^{\!\!\circ}|\mathsf{HX}$ setup.

LENS Lens

STANDARD

IP Protocol

PHYSICAL

| Camera Control | Protocol: VISCA Over IP |
|----------------|--|
| Operation Temp | 32°F - 104°F |
| Dimension | 90mm x 24mm |
| | 3.5" x 0.94" (with default WP cap) |
| Weight | 180g / 0.39lbs (with default WP cap) |
| Power | 12VDC (+9 - +15VDC) (PoE Adapter Included) |

UDP|IP, RTSP|RTMP, SRT, NDI|HX

M12 (Default 4mm HD Lens with WP CAP)

*Specification are subject to change without notice.

PACKAGE CONTENTS



PoE Dongle Adapter



DC 12v Power Supply & Sockets Adapter



*NDI® is a registered trademark of Newtek, Inc.

At ADIA Imaging, innovation is key to crafting our tried and tested quality imaging solutions. We strive to raise the bar by engineering and manufacturing cutting edge cameras and converters. From concept to reality, AIDA Imaging meticulously creates products that are applicable to various solutions, effective for the global user.