

# Ikegami

## Multiformat 3G SDI Monitor

### ULE-315

After many successful years of providing the broadcast industry with its cost-effective ULE-Monitor series, Ikegami now adds a brand new 31.5 Inch model to their current HD monitor line-up. The ULE-315 is a professional multi-purpose Full-HD monitor with a variety of in- and outputs, low weight, compact dimensions and standardized VESA mounts, which makes it the ideal solution for professional broadcast installations at a reasonable price. Many convenient features such as 16 Audio-Meters for embedded audio, built-in speakers, markers and pixel-by-pixel mode are featured as standard. To ensure a precise and consistent image quality, the ULE-315 can be colour calibrated with measuring probes of established manufacturers and implements an AHVA (IPS-Type) panel for super wide viewing angles.



#### Convenient Features

- Colour Calibration
- AHVA (IPS-Type) Panel
- Built-In Speakers
- Blue / Mono Mode
- Marker, Safety Area
- 3G-SDI 425M-A (YCbCr 4:2:2) (2 In / 1 Out)
- HDMI, DVI, VGA, Component (3 BNC)
- SDI Active Loop-Through
- Pixel-By-Pixel, Zero Scan, Over Scan
- SDI Embedded 16ch Audio Level Meters

#### Input Format

1080p (60/59.94/50/30/29.97/25/24/23.98), 1080i(60/59.94/50), 1080Psf (30/29.97/25/24/23.98)  
2048x1080p(24/23.98/24sF/23.98sF), 1035i(60/59.94)  
720p(60/59.94/50/30/29.97/25/24/23.98)  
625i(PAL 50), 525i(NTSC 59.94), 480i/480p/576i/576p

#### Interface

SDI In / Out	2 / 1
HDMI In	1
DVI In	1
VGA In	1
Component In	1
Audio In	1

#### Display

Screen Size	31.5"
Resolution	1920x1080
Brightness	400 cd/m <sup>2</sup>
Contrast Ratio	3000:1
Panel Type	AHVA (IPS-Type)
Viewing Angle	178° / 178°

#### General

Electrical Rating	AC 100-240V
Power Consumpt.	50 W
Oper. Temp.	0 - 40 °C
Dimensions(mm)	744 x 502 x 160
Weight	12 kg
MTBF (aprox.)	33.000 hours

Design and specifications are subject to change without notice.



**Ikegami** IKEGAMI ELECTRONICS (EUROPE) GMBH

■ URL [www.ikegami.de](http://www.ikegami.de)

HEADQUARTERS Ikegamistr. 1, 41460 Neuss, Germany  
Phone: +49-(0)2131-1230 / Fax: +49(0)2131-102820

