





Wooden Camera | Anton/Bauer

26V Gold Mount Plus

ARRI Alexa LF, 65, SXT

Attaches one 26V battery to the back of the ARRI Alexa LF, 65, and SXT cameras. Prioritized 2pin DC input to support block batteries with hot-swap backup and OLED screen for voltage information. Includes two regulated 15V P-Tap ports.



Wooden Camera | Anton/Bauer

26V Gold Mount Plus Sharkfin Battery Bracket

ARRI Alexa LF. 65. SXT

Attaches two 26V batteries directly to the back of the ARRI Alexa LF, 65, and SXT cameras. Prioritized 2pin DC input to support block batteries with hot-swap backup and OLED screen for voltage information. Includes two regulated 15V P-Tap ports.



Litepanels | Anton/Bauer

26V Gold Mount Plus Dual Battery Brackets

3-Pin / 4-Pin XLR Output

26V Dual Battery Bracket for high-power LED lighting such as the Litepanels Gemini 2x1, ARRI SkyPanels or similar fixtures. Run lights at full intensity using two hot-swappable Anton/Bauer 26V batteries.



Anton/Bauer

26V Gold Mount Plus Dual Voltage Quad Charger

For Gold Mount Plus and regular Gold Mount Batteries

Simultaneously charge up to four 14.4V Gold Mount or 26V Gold Mount Plus batteries. Anton/Bauer smart charging technology can rapidly charge 26V batteries faster than standard 14.4 chargers, bringing a DIONIC 26V 98Wh battery to full charge in just 1.5hrs.



Anton/Bauer

26V Gold Mount Plus Quad Discharger

For Gold Mount Plus and regular Gold Mount Batteries

Dedicated 26V discharge unit that quickly and safely discharges up to four 14.4V Gold Mount or 26V Gold Mount Plus batteries to less than 30% to meet IATA travel regulations.

High-powered, versatile, travel-safe

Power on set

Available in 98Wh and 240Wh versions, Anton/Bauer smart battery technology combined with high energy cells provides consistent power with protection from over-voltage, short-circuits and heat. Have confidence that your equipment will always be ready when you need it. Know your battery runtime down to the minute with the on-board LCD display or in your camera viewfinder.

The Gold Mount *Plus* mount on DIONIC 26V batteries is not only the industry's most secure battery lock system but also enables the most reliable communications between the battery and a camera or light. The Gold Mount *Plus* lock system protects sensitive equipment from overcharge with a unique pin configuration designed to prevent overpowered batteries from connecting.

When your production demands that your equipment runs at peak performance, DIONIC 26V batteries ensure that you have the power.

Smart Technology

Over-discharge, over-voltage, short circuit and thermal protection.

Gold Mount Plus

Most secure battery mount and reliable communications between battery and powered device.

On-board LCD Screen

Knowledge is power, know your runtime down to the minute.







Batteries Gold Mount Plus





| oni | | | |
|-----|--|--|--|
| | | | |
| | | | |

Dionic 26V 240Wh

| Capacity | 99Wh | 250Wh | | |
|-----------------------------|--|--|--|--|
| Available Mounts | Gold Mount Plus | | | |
| Dimensions (WxHxD) | 3.9"x 5.2" x 2.8" / 9.9cm x 13.1cm x 7.1cm | 3.4"x 3.9" x 5.2" / 9.9cm x 13.1cm x 8.7cm | | |
| Weight | 2.05lbs. / 0.93kg | 3lbs. / 1.36kg | | |
| Current | 12A Constant | | | |
| Operating temperature range | -4°F to 140°F / -20°C to 60°C | | | |
| Output Voltage | 17.5V - 28.9V or 25.4V | 17.5V - 29.4V or 25.2V Nominal | | |
| Charge time | ~1.5 hours to 100% | ~3.5 hours to 100% | | |
| Warranty | 2 Years | | | |



Supply Voltage





LP4 Quad Gold Mount Plus Charger

LPD Quad Gold Mount Plus Discharger

None

| Available Mounts | Gold Mount Plus | | | |
|-----------------------------|---|--|--|--|
| Dimensions (WxHxD) | 9" x 3.6" x 12.2" / 22.9cm x 9.1cm x 31cm | 12.1" x 3.6" x 9" / 31cm x 9.1cm x 2.3cm | | |
| Weight | 4.7lbs. / 2.13kg | 4.2lbs. / 1.9kg | | |
| Operating temperature range | -4°F to 140°F / -20°C to 60°C | | | |

100-240 VAC, 50/60 Hz

The Anton/Bauer 26V Advantage

More efficient and effective than dual voltage batteries, DIONIC 26V batteries feature a design dedicated to one voltage to deliver a longer battery lifetime and less heat for a stronger battery. With 12A power output, DIONIC 26V batteries are able to drive high-powered accessories including follow-focus, servo motors and wireless transmitters. No matter how demanding your camera, lights or accessories are, with DIONIC 26V you have the power.



Technical Support

At Vitec Production Solutions we take great pride in the quality of our products and we also recognize that your experience with our products will be even more positive and productive with strong, effective support to back them up. Vitec Production Solutions Service Centers are there to provide technical support for customers and partners, via telephone or email. For more information, including complete contact details, please go to: www.vitecsupport.com